

## IMALACK 2047 M41

<b>DESCRIPTION</b>	Aliphatic PU resins-based finish, in solvent mixture. Matt. Fat touch.	
<b>USE</b>	It shall be used on polyurethane artificial leathers by 1000 point cylinder.	
<b>Characteristics of the product</b>	<i>Aspect:</i>	Vealed slightly yellow liquid
	<i>Dry Content:</i>	25,00± 1%
	<i>Solvent/s</i>	IBA/TOL/Glycoethers
	<i>Viscosity:</i>	15 - 25 sec. F.C.6
<b>Modifiers</b>	<i>For the pigmentation</i>	NOVA TC
	<i>To increase the matt effect</i>	IMASTER 016/AV, IMASTER OGS
	<i>To increase the fat touch</i>	IMAFAT OPM, IMACEL 4
	<i>To decrease the matt effect</i>	IMALACK 2000
<b>Packing</b>	<i>Metal drums of Kgs:</i>	180
<b>Storage</b>	The product must be stored at temperatures between -1 °C and 30 °C. In this conditions the product is stable for 6 months	
<b>Notes</b>	STIR WELL BEFORE USE KEEP PACKINGS PERFECTLY SEALED	

<b>Legend</b>	N.A. = NOT APPLICABLE	N.D. = NON DETERMINED	F.C. = FORD CUP
<i>First issuing date:</i>	29/05/2017	<i>Revision date:</i>	29/05/2017
		<i>Revision nr.:</i>	
		<i>Print date:</i>	31/07/2017