

IMALACK 2084/O

DESCRIPTION

Aliphatic PU resins-based finish, in solvent mixture.
Matt.

USE

The product has to be applied by 1000 points roll on PU or PVC.

Characteristics of the product

<i>Aspect:</i>	Whitish viscous liquid
<i>Dry Content:</i>	11,00%± 1
<i>Solvent/s</i>	IBA/TOL/DMF
<i>Viscosity (25 °C)</i>	N.A.

Modifiers

<i>For the pigmentation</i>	NOVA TC ND
<i>For the colouring</i>	IMACOLOR

Packing

<i>Metal drums of Kgs:</i>	180
----------------------------	-----

Storage

The product must be stored at temperatures between -1 °C and 30 °C. In this conditions the product is stable for 6 months

Notes

KEEP PACKINGS PERFECTLY SEALED
STIR WELL BEFORE USE

Legend	N.A. = NOT APPLIABLE	N.D. = NON DETERMINED	F.C. = FORD CUP				
<i>First issuing date:</i>	11/11/2020	<i>Revision date:</i>	11/11/2020	<i>Revision nr.:</i>		<i>Print date:</i>	11/11/2020

Our technical advices, whether verbal or in writing, are based on data considered correct. No warranty is anyhow granted, neither concerning the immunity for eventual applications in conflict with existing patents. The user is required to check that the product supplied is suitable for the processes and uses to which it is destined and because the circumstances and processing of the product are beyond our control, we do not assume any responsibility for any loss or damage eventually occurred. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered and used. The quality of the products supplied will be in accordance to the standards, according to what reported in our general sales conditions.