

IMALACK NTS 08

DESCRIPTION	Cellulose esters-based finish, in solvent mixture. Nitro lacker. Matt effect and fat touch.	
USE	Suitable for the finishing of polyurethane coagulated materials, destined to the manufacturing of labels embossable by heat.	
Characteristics of the product	<i>Aspect:</i>	Yellowish liquid
	<i>Dry Content:</i>	20,00± 1%
	<i>Solvent/s</i>	MEK/IPA/PM1
	<i>Viscosity 25 °C:</i>	90 sec. C.F. 4
Modifiers	<i>For dilution</i>	ESTERS, TOL
	<i>For a fat touch</i>	IMACEL 4
	<i>For the pigmentation</i>	NOVA TC
	<i>For the colouring</i>	IMANIL WSA
Storage	The product must be stored at temperatures between -1 °C and 30 °C. In this conditions the product is stable for 6 months	
Notes	STIR WELL BEFORE USE KEEP PACKINGS PERFECTLY SEALED	

Legend	N.A. = NOT APPLICABLE	N.D. = NON DETERMINED	F.C. = FORD CUP		
<i>First issuing date:</i>	20/10/2008	<i>Revision date:</i>	<i>Revision nr.:</i>	<i>Print date:</i>	09/08/2022
