

## IMALACK NTS 90

<b>DESCRIPTION</b>	Cellulose esters-based finish, in solvent mixture. Nitro lacker. Gloss effect.	
<b>USE</b>	Suitable for the finishing of polyurethane coagulated materials, destined to the manufacturing of labels embossable by heat.	
<b>Characteristics of the product</b>	<i>Aspect:</i>	Yellowish liquid
	<i>Dry Content:</i>	20,00± 1%
	<i>Solvent/s</i>	MEK/IPA/PM1
	<i>Viscosity 25 °C:</i>	90 sec. C.F.4
<b>Modifiers</b>	<i>For dilution</i>	ESTERS, TOL
	<i>For a fat touch</i>	IMACEL 4
	<i>For the pigmentation</i>	NOVA TC
	<i>For the colouring</i>	IMACOLOR
<b>Storage</b>	The product must be stored at temperatures between -1 °C and 30 °C. In this conditions the product is stable for 6 months	
<b>Notes</b>	STIR WELL BEFORE USE KEEP PACKINGS PERFECTLY SEALED	

---

<b>Legend</b>	N.A. = NOT APPLIABLE	N.D. = NON DETERMINED	F.C. = FORD CUP		
<i>First issuing date:</i>	20/10/2008	<i>Revision date:</i>	<i>Revision nr.:</i>	<i>Print date:</i>	09/08/2022

---