

IMALACK VA 271/AE

DESCRIPTION Vinyl-acrylic resins-based finish, in solvent mixture (DMF free).
Glossy, sliding touch, good adhesion to PVC, good barrier to plasticizers migration.

USE It shall be applied by 1000 points cylinder on plasticized-PVC-based artificial leathers.

Characteristics of the product	<i>Aspect:</i>	Matte liquid
	<i>Dry Content:</i>	30,00%± 1
	<i>Solvent/s</i>	EA
	<i>Viscosity:</i>	1000 - 3000 mPa.s

Modifiers	<i>To increase the sliding</i>	IMASIL 132, IMASIL 136
	<i>For a matt effect</i>	IMASTER 20, IMASTER 016 AV
	<i>For a fat touch</i>	IMAFAT OPM, IMACEL 4
	<i>For the pigmentation</i>	NOVA TC ND
	<i>For the colouring</i>	IMACOLOR

Packing	<i>Metal drums of Kgs:</i>	180
----------------	----------------------------	-----

Storage The product must be stored at temperatures between -1 °C and 30 °C. In these conditions the product is stable for 6 months

Notes STIR WELL BEFORE USE
KEEP PACKINGS PERFECTLY SEALED

Legend	N.A. = NOT APPLICABLE	N.D. = NON DETERMINED	F.C. = FORD CUP				
<i>First issuing date:</i>	09/07/2018	<i>Revision date:</i>	09/07/2018	<i>Revision nr.:</i>		<i>Print date:</i>	14/09/2018

Our technical advices, whether verbal or in writing, are based on data considered correct. No warranty is anyhow granted, neither concerning the immunity for eventual applications in conflict with existing patents. The user is required to check that the product supplied is suitable for the processes and uses to which it is destined and because the circumstances and processing of the product are beyond our control, we do not assume any responsibility for any loss or damage eventually occurred. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered and used. The quality of the products supplied will be in accordance to the standards, according to what reported in our general sales conditions.