

## IMALACK VNF/BV-DF

### DESCRIPTION

Vinyl-acrylic resins-based finish, in solvent mixture.  
Good adhesion to PVC. No blocking. Phthalates-free.

### USE

It shall be applied by 1000 points cylinder on PVC articles.  
The product can be used also as top-skin.

### Characteristics of the product

<i>Aspect:</i>	Viscous liquid
<i>Dry Content:</i>	25,00%± 1
<i>Solvent/s</i>	TOL/AE/Dioxolane
<i>Viscosity (25 °C)</i>	1000 - 3000 mPa.s

### Modifiers

<i>For dilution</i>	ESTERS, TOL, DMF
<i>For the pigmentation</i>	NOVA TC ND
<i>For the colouring</i>	IMACOLOR

### Packing

<i>Metal drums of Kgs:</i>	180
----------------------------	-----

### Storage

The product must be stored at temperatures between 1 °C and 30 °C. In these conditions the product is stable for 6 months

### Notes

STIR WELL BEFORE USE  
KEEP PACKINGS PERFECTLY SEALED

---

<b>Legend</b>	N.A. = NOT APPLIABLE	N.D. = NON DETERMINED	F.C. = FORD CUP				
<i>First issuing date:</i>	21/11/2017	<i>Revision date:</i>	23/02/2021	<i>Revision nr.:</i>	1	<i>Print date:</i>	12/02/2024

---