

IMALACK W 30 MATT

DESCRIPTION	Matt aliphatic PU resins-based finish, water-born. Matt, soft film.	
USE	The product can be applied by 1000 points or reverse-roll on PU or PVC articles.	
Characteristics of the product	<i>Aspect:</i>	Milky viscous liquid
	<i>Dry Content:</i>	25,00± 1%
	<i>Solvent/s</i>	H2O
	<i>Viscosity 25 °C:</i>	NA
Modifiers	<i>For the cross-linking</i>	IMACAT 207
	<i>For the pigmentation</i>	NOVA W
	<i>For the rheology</i>	IMACOAT 42
	<i>For a sliding touch</i>	IMASIL WS 1009
Packing	<i>Metal drums of Kgs:</i>	200
	<i>PE drums of Kgs:</i>	100
Storage	The product must be stored at temperatures between 5 °C and 30 °C. In this conditions the product is stable for 6 months	
Notes	STIR WELL BEFORE USE SHELTER FROM FROST KEEP PACKINGS PERFECTLY SEALED	

Legend	N.A. = NOT APPLIABLE	N.D. = NON DETERMINED	F.C. = FORD CUP		
<i>First issuing date:</i>	13/04/2022	<i>Revision date:</i>	<i>Revision nr.:</i>	<i>Print date:</i>	01/07/2022
